

軸 部			翼 部			N'の適用範囲	
径 D(mm)	厚さ t (mm)	翼部が取り付けられる部分の厚さ t ₁ (mm)	径 Dw(mm)	材質	厚さ t ₂ (mm)		
89.1	2.8 以上	4.2以上 (STK400) 3.5以上 (STK490)	300	SS400	9	3≦N'≦ 11	3≦N'≦ 8
				SM490A	12	3≦N'≦ 15	3≦N'≦ 15
			400	SS400	9	3≦N'≦ 9.5	3≦N'≦ 7
					12	3≦N'≦ 11.5	3≦N'≦ 8.5
SM490A	3≦N'≦ 15	3≦N'≦ 13					
101.6	3.2 以上	4.2以上 (STK400) 3.5以上 (STK490)	300	SS400	9	3≦N'≦ 11.5	3≦N'≦ 8.5
				SM490A	12	3≦N'≦ 15	3≦N'≦ 15
			400	SS400	9	3≦N'≦ 10.5	3≦N'≦ 7.5
					12	3≦N'≦ 12.5	3≦N'≦ 9
				SM490A		3≦N'≦ 15	3≦N'≦ 13.5
				500	SS400	9	3≦N'≦ 7
			12			3≦N'≦ 10	3≦N'≦ 7.5
			114.3	3.5 以上	4.5以上 (STK400) 3.5以上 (STK490)	300	SS400
SM490A	12	3≦N'≦ 15					3≦N'≦ 15
400	SS400	9				3≦N'≦ 10.5	3≦N'≦ 8
		12				3≦N'≦ 13	3≦N'≦ 10
	SM490A					3≦N'≦ 15	3≦N'≦ 13
	500	SS400				9	3≦N'≦ 9
12						3≦N'≦ 11.5	3≦N'≦ 8.5
9						3≦N'≦ 6.5	3≦N'≦ 5
12						3≦N'≦ 8.5	3≦N'≦ 6.5
139.8	3.5 以上	4.5以上 (STK400) 3.5以上 (STK490)				300	SS400
			SM490A	12	3≦N'≦ 15		3≦N'≦ 15
			400	SS400	9	3≦N'≦ 10.5	3≦N'≦ 8
					12	3≦N'≦ 13	3≦N'≦ 10
				SM490A		3≦N'≦ 15	3≦N'≦ 13
				500	SS400	9	3≦N'≦ 9
			12			3≦N'≦ 11.5	3≦N'≦ 8.5
			9			3≦N'≦ 6.5	3≦N'≦ 5
			12			3≦N'≦ 8.5	3≦N'≦ 6.5