

軸 部			翼 部			N'の適用範囲	
径 D(mm)	厚さ t (mm)	翼部が取り 付けられる 部分の厚さ t ₁ (mm)	径 Dw(mm)	材質	厚さ t ₂ (mm)		
89.1	2.8 以上	4.2以上 (STK400) 3.5以上 (STK490)	300	SS400	9	2≦N'≦ 11	2≦N'≦ 8
				SM490A	12	2≦N'≦ 12.5	2≦N'≦ 12.5
			400	SS400	9	2≦N'≦ 9.5	2≦N'≦ 7
					12	2≦N'≦ 11.5	2≦N'≦ 8.5
SM490A	2≦N'≦ 12.5	2≦N'≦ 12.5					
101.6	3.2 以上	4.2以上 (STK400) 3.5以上 (STK490)	300	SS400	9	2≦N'≦ 11.5	2≦N'≦ 8.5
				SM490A	12	2≦N'≦ 12.5	2≦N'≦ 12.5
			400	SS400	9	2≦N'≦ 10.5	2≦N'≦ 7.5
					12	2≦N'≦ 12.5	2≦N'≦ 9
				SM490A		2≦N'≦ 12.5	2≦N'≦ 12.5
			500	SS400	9	2≦N'≦ 7	2≦N'≦ 5
					12	2≦N'≦ 10	2≦N'≦ 7.5
				114.3	3.5 以上	4.5以上 (STK400) 3.5以上 (STK490)	300
SM490A	12	2≦N'≦ 12.5	2≦N'≦ 12.5				
400	SS400	9	2≦N'≦ 10.5				2≦N'≦ 8
		12	2≦N'≦ 12.5				2≦N'≦ 10
	SM490A		2≦N'≦ 12.5				2≦N'≦ 12.5
500	SS400	9	2≦N'≦ 9				2≦N'≦ 6.5
		12	2≦N'≦ 11.5				2≦N'≦ 8.5
		9	2≦N'≦ 6.5				2≦N'≦ 5
		12	2≦N'≦ 8.5	2≦N'≦ 6.5			
139.8	3.5 以上	4.5以上 (STK400) 3.5以上 (STK490)	300	SS400	9	2≦N'≦ 9.5	2≦N'≦ 7
				SM490A	12	2≦N'≦ 12.5	2≦N'≦ 12.5
			400	SS400	9	2≦N'≦ 10.5	2≦N'≦ 8
					12	2≦N'≦ 12.5	2≦N'≦ 10
				SM490A		2≦N'≦ 12.5	2≦N'≦ 12.5
			500	SS400	9	2≦N'≦ 9	2≦N'≦ 6.5
					12	2≦N'≦ 11.5	2≦N'≦ 8.5
					9	2≦N'≦ 6.5	2≦N'≦ 5
12	2≦N'≦ 8.5	2≦N'≦ 6.5					